


Unitube Versa Cables for use in Microducts

Cable Design

IEC/EN 60794



- not to scale -

- **Fibres:** see datasheet CFS09011 for G.657.A1 and CFS09003 for G.657.A2.
- **Loose Tube:** thermoplastic material, containing up to 12 fibres and filled with a suitable gel compound.
- **Water Tightness:** fully watertight construction.
- **Strength members:** aramid yarns are applied in the cable.
- **Outer sheath:** high-density polyethylene compound, halogen free.

This unitube dielectric optical cable is designed for outdoor installation in ducts and microducts by blowing techniques.

Technical data

No. and Type of Fibres		2 x G.657.A2	4 x G.657.A2	12 x G.657.A1
Design		1 x 2	1 x 4	1 x 12
Cable Diameter	mm	2.9		3.2
Cable Weight	kg / km	6.8		8.2

Main characteristics

Test	Standard	Specified value	Acceptance Criteria ⁽³⁾
Tensile Performance	IEC 60794-1-2-E1	250N	$\Delta\alpha \leq 0.05$ dB
Crush	IEC 60794-1-2-E3	1250N, 100mm plate/plate 1min.	$\Delta\alpha \leq 0.05$ dB
Impact	IEC 60794-1-2-E4	3 Nm, R=200mm, 3 impacts	$\Delta\alpha \leq 0.05$ dB
Repeated bending	IEC 60794-1-2-E6	R= 15x cable Ø, 100 cycles, 20N	$\Delta\alpha \leq 0.05$ dB
Cable bend	IEC 60794-1-2-E11	R= 10x cable Ø, 5 turns, 3 cycles ⁽¹⁾	$\Delta\alpha \leq 0.05$ dB
Temperature range ⁽²⁾	IEC 60794-1-2-F1	-30 to +60°C -40 to +70°C	$\Delta\alpha \leq 0.05$ dB/km $\Delta\alpha$ reversible
Water Penetration	IEC 60794-1-2-F5B	sample=3m, water=1m	no water leakage after 24h
Min. bending radius	mm	Without Tension 10 x Cable-Ø	Under Maximum Tension 25 x Cable-Ø
Temperature range	°C	Installation -15 to +50	Transport. & Storage -40 to +70 Operation -40 to +60

⁽¹⁾ at room temperature 23°C ± 2°C ⁽²⁾ temperature cycling test shall be performed on cable coil (without drum)













⁽³⁾ all optical measurements at 1550 nm.

Optical Characteristics

See attached cabled optical fibre data sheet for G.657.A1 and G.657.A2 fibres.

Identification

Fibre Colours

No.	1	2	3	4	5	6	7	8	9	10	11	12
Colour	red	blue	white	green	yellow	grey	brown	black	violet	orange	aqua	pink
												

Sheath Colour:

The outer sheath colour is yellow.

Sheath Marking:

The outer sheath is marked in 1 meter intervals as follows:

**RALA DRAKA(DL) JN-SM-URE<dd>/GOGLDV <fibre count> x <fibre type> S12
Idno.<cable ID> <year> <length marking>m**

<dd>: cable diameter in tenths of millimetre

Logistic

Packing:

Plastic or Plywood drums with protection

Delivery Lengths:

Standard delivery lengths are 4 km with a tolerance of -1% / +3%

© PrysmianGroup 2017, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by PrysmianGroup: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of PrysmianGroup. The information is believed to be correct at the time of issue. PrysmianGroup reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorized by PrysmianGroup.